

SHELL HELIX DIESEL HX5

15W-40 PREMIUM MULTI-GRADE MOTOR OIL
CLEANS AND PROTECTS FOR REDUCED ENGINE NOISE AND VIBRATION



DESIGNED TO MEET CHALLENGES

Shell Helix Diesel HX5 has been formulated with cleansing technology. It uses special active cleansing technology to help engines operate effectively for a smoother and quieter drive.

PERFORMANCE FEATURES

FORMULATED WITH CLEANSING TECHNOLOGY

- Works harder to protect than ordinary motor oils by continuously helping to prevent soot deposits from building up on engine surfaces.

GOOD OXIDATION STABILITY

- Resists oil degradation throughout the oil drain interval.

HIGH QUALITY BASE OILS

- Helps reduce the oil volatility and therefore the oil consumption.

MINIMISES VIBRATION AND ENGINE NOISE

- Smoother, quieter drive.

APPLICATION

DIESEL ENGINES

- Suitable for naturally aspirated or turbo-charged indirect injection diesel engines. These engines produce more power than older engines and therefore run hotter. Hotter engines can produce more dirt and sludge.

SPECIFICATIONS, APPROVALS AND RECOMMENDATIONS

Shell Helix Diesel HX5 is suitable for use where the following specifications are called for:

- API: CF
- ACEA: B2.

TYPICAL PHYSICAL CHARACTERISTICS

CHARACTERISTICS	15W-40
Kinematic Viscosity (IP 71)	
@ 40°C mm ² /s	105.4
@ 100°C mm ² /s	13.9
Viscosity Index (IP 226)	132
Density @ 15 kg/m ³ (IP 365)	885
Flash Point °C (IP 34)	220
Pour Point °C (IP 15)	-30

Shell
HELIX
Motor oils