

# SHELL HELIX HX3

20W-50 MULTI-GRADE MOTOR OIL  
CLEANS AND PROTECTS OLDER ENGINES



DESIGNED TO MEET CHALLENGES

Shell Helix HX3 has been formulated with cleansing technology to help stop dirt and sludge building up and therefore help protect and prolong the life of the engine.

## PERFORMANCE FEATURES

FORMULATED TO REMOVE ENGINE DEPOSITS

- Helps to protect and prolong the life of the engine.

OXIDATION RESISTANCE

- Resists oil degradation throughout the oil drain interval.

MULTI-GRADE VISCOSITY

- Easier cold starting compared with mono-grade oils.
- Helps reduce oil consumption.

## APPLICATIONS

PETROL AND DIESEL ENGINES

- Shell Helix HX3 is suitable for petrol engines fitted with conventional carburettors.
- Also suitable for naturally aspirated or turbo-charged indirect diesel engines.
- Formulated with cleansing technology to help stop dirt and sludge building up.

## SPECIFICATIONS, APPROVALS AND RECOMMENDATIONS

Shell Helix HX3 is suitable for use where the following specifications are called for:

- API: SJ/CF.

### TYPICAL PHYSICAL CHARACTERISTICS

CHARACTERISTICS	20W-50
Kinematic Viscosity (IP 71)	
@ 40°C mm <sup>2</sup> /s	157
@ 100°C mm <sup>2</sup> /s	19.0
Viscosity Index (IP 226)	137
Density @ 15 kg/m <sup>3</sup> (IP 365)	888
Flash Point °C (PMCC) (IP 34)	215
Pour Point °C (IP 15)	-27

Shell  
**HELIX**  
Motor oils